AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Previously Presented) In a process for foaming polyurethanes comprising adding CFC 11 to compositions used to make solid polymers to give a homogeneous foam having density of about 30 Kg/cm³, the improvement comprising substituting CFC 11 in its entirety with azeotropic or near azeotropic foaming agents compositions, wherein said foaming agent compositions are selected from the group consisting of:

		Composition
		% by weight
IV)	difluoromethoxy	
	bis(difluoromethyl ether)	1-99
	(HCF ₂ OCF ₂ OCF ₂ H);	
	1,1,1,3,3-pentafluorobutane	99-1
	(CF ₃ CH ₂ CF ₂ CH ₃ , HFC 365mfc)	
V)	difluoromethoxy	
	bis(difluoromethyl ether)	1-40
	(HCF ₂ OCF ₂ OCF ₂ H);	
	1,1,1,4,4,4-hexafluorobutane	99-60
	(CF ₃ CH ₂ CH ₂ CF ₃ , HFC 365ffa)	

and wherein the difluoromethoxy-bis(difluoromethyl ether) part optionally contains up to 40% by weight of 1-difluoromethoxy-1,1,2,2-tetrafluoroethyldifluoromethyl ether based on total quantity of the difluoromethoxy-bis(difluoromethyl ether).

2. (Original) The process of claim 1, wherein said foaming agent compositions are selected from the group consisting of:

composition

% by weight

IV) difluoromethoxy

bis(difluoromethyl ether)

10-98

(HCF2OCF2OCF2H);

1,1,1,3,3-pentafluorobutane

90-2

(CF₃CH₂CF₂ CH₃, HFC 365 mfc)

V) difluoromethoxy

bis(difluoromethyl ether)

10-40

(HCF2OCF2OCF2H);

1,1,1,4,4,4-hexafluorobutane

90-60

(CF₃CH₂CH₂ CF₃, HCF 356 ffa).

3. (Original) The process of claim 1, wherein said foaming agent compositions are selected from the group consisting of:

composition

% by weight

D) difluoromethoxy

bis(difluoromethyl ether)

60 % by wt.

(HCF2OCF2OCF2H);

1,1,1,3,3-pentafluorobutane

40 % by wt.

(CF₃CH₂CF₂ CH₃, HFC 365 mfc)

E) difluoromethoxy

bis(difluoromethyl ether)

20 % by wt.

(HCF2OCF2OCF2H);

1,1,1,4,4,4-hexafluorobutane

80 % by wt.

(CF₃CH₂CH₂CF₃, HCF 356 ffa).

- 4. (Original) The process according to claim 1, wherein said compositions are added in amounts in the range 1-15% by weight on the total preparation.
- 5. (Original) The process according to claim 1, wherein said compositions are used in combination with H_2O and/or CO_2 .
- 6. (Previously Presented) The process according to claim 5, wherein the water amount is in the range 0.5-7 parts by weight on one hundred parts of polyol.
- 7. (Original) The process according to claim 5, wherein the CO_2 amount is in the range 0.6-10 parts by weight on one hundred parts of polyol.
- 8. (Original) The process according to claim 5, wherein stabilizers for radicalic decomposition reactions are added, the concentration of which is in the range 0.1-5% by weight with respect to the foaming agent.
- 9. (Previously Presented) In polyurethane polymer foaming compositions comprising CFC-11 to give a homogeneous foam having density of about 30 Kg/cm³, the improvement comprising the substitution of CFC-11 in its entirety with foaming agent azeotropic or near azeotropic compositions selected from the group consisting of:

composition

% by weight

IV) difluoromethoxy

bis(difluoromethyl ether) 1-99

(HCF2OCF2OCF2H);

1,1,1,3,3-pentafluorobutane 99-1

(CF₃CH₂CF₂ CH₃, HFC 365 mfc)

V) difluoromethoxy

bis(difluoromethyl ether)

1-40

(HCF2OCF2OCF2H);

1,1,1,4,4,4-hexafluorobutane

99-60

(CF₃CH₂ CH₂CF₃, HCF 356 ffa).

wherein the diflouromethoxy-bis (difluoromethyl ether) parts optionally contains up to 40% by weight of 1-difluoromethoxy-1,1,2,2-tetrafluoroethyldifluoromethyl ether based on total quantity of the difluoromethoxy-bis(difluoromethyl ether).

10. (Original) Polyurethane polymer foaming compositions according to claim 9 comprising foaming agent selected from the group consisting of:

composition

% by weight

D) difluoromethoxy

bis(difluoromethyl ether)

60 % by wt.

(HCF2OCF2OCF2H);

1,1,1,3,3-pentafluorobutane

40 % by wt.

(CF₃CH₂CF₂ CH₃, HFC 365 mfc)

E) difluoromethoxy

bis(difluoromethyl ether)

20 % by wt.

(HCF2OCF2OCF2H);

1,1,1,4,4,4-hexafluorobutane

80 % by wt.

(CF₃CH₂CH₂ CF₃, HCF 356 ffa).

11. (New) Azeotropic foaming agents compositions selected from the group consisting of:

Composition

% by weight

IV) difluoromethoxy

bis(difluoromethyl ether)

(HCF₂OCF₂OCF₂H);

1,1,1,3,3-pentafluorobutane

(CF₃CH₂CF₂ CH₃, HFC 365mfc)

V) difluoromethoxy
bis(difluoromethyl ether)

(HCF₂OCF₂OCF₂H);

1,1,1,4,4,4-hexafluorobutane

(CF₃CH₂CH₂ CF₃, HFC 365ffa)

and wherein the difluoromethoxy-bis(difluoromethyl ether) part optionally contains up to 40% by weight of 1-difluoromethoxy-1,1,2,2-tetrafluoroethyldifluoromethyl ether based on total quantity of the difluoromethoxy-bis(difluoromethyl ether).